

The Atex certified four load cell weight detection IP68 guarantees the best accuracy in all work conditions.
Available also CE-M APPROVED.

Features:

- Maximum lifting capacity: 2500 kg.
- Accuracy: +/- 0.05% of applied load.
- Fork dimensions 1170 x 550 x 85 mm.
- Bearing structure in extra thick sheet steel and oven-fire painted interior construction.
- Standard fitted swiveling column.
- Rubber steering wheels and double loading rollers in Polyurethane.
- ATEX certified, 4 stainless steel IP68 shear-beam load cells.
- Indicator with easy to clean satined stainless steel case with IP68 enclosure built to withstand humid and dusty environments; large LCD display 25-mm high contrast digits which are clearly visible even in poor lighting conditions; 16-key numerical/functional membrane waterproof keyboard.
- Calibration and Set-Up parameters configurable from keyboard.
- Power supply through extractable battery, rechargeable in safe zone.
- 150-hour approximate operating time.
- Equipped with 230Vac 50 Hz battery charger to be recharged in a safe area.

Selectable Functions:

- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weighs accumulation
- Formulation
- Counting
- In/Out weighing
- Hold.

Keyboard functions:

- Zeroing
- Automatic Tare
- Presetable Tare
- ID1 and ID2 10-digit Codes
- Print and data transmission commands
- selectable function command
- On/Off switching

Options only available at time of order:

- Rechargeable battery kit.
- Parking brake system with command pedal mounted on steering wheels.
- Set of steering wheels in Vulkolan (nonstainable).
- 680 mm fork width (ask for price estimate).
- Special fork length from 850 to 1500 mm (ask for price estimate).
- 3000 kg capacity (ask for price estimate).
- Special models and sizes (ask for estimate).